

# ROTATING PULVERIZERS



## HIGH QUALITY MATERIAL

-built with high quality steel for maximum strength and abrasion resistance.

## SPEED VALVE

-improves cycle time by up to 30% compared to standard hydraulic system.

## EXCHANGEABLE TOOTH PLATE

-eliminates the need to build up and hardface and are fast and easy to change in the field.



## LARGE-BORE CYLINDER

-the single large diameter cylinder with speed valve provides exceptional cutting and crushing force.

## 360° HYDRAULIC ROTATION

-provides fast and precise positioning of the jaws.



HYD.ROTATION



SPEED VALVE



HARDOX WEAR PLATE

## SPECIFICATIONS

Model	Unit	TP15RV	TP20RV	TP25RV	TP30RV	
Carrier Weight	ton	10 - 18	18 - 26	23 - 30	29 - 35	
Operating Weight	kg	1,200	1,950	2,250	2,800	
Height	mm	1850	2090	2478	2850	
Width		480	520	540	600	
Jaw Opening		790	920	935	1100	
Jaw Depth		820	865	870	900	
Blade Length		140	150	200	200	
Cutting Force at Blade	ton	163	186	202	257	
Crushing Force at Tip	ton	42	54	62	92	
Max. Oil Pressure	bar	300	320	320	320	
Oil Flow Rate	lpm	100-180	180-220	210-240	240-280	
Jaw open / close	sec	2.4/2.4	2.6/2.8	2.7/2.9	2.7/3.0	
Hyd. Rotation	Pressure	bar	180	210	210	210
	Oil Flow	lpm	28-32	30-38	32-45	32-45

Specifications are subject to change without notice